

AQUA ACRIL PRIMER – AS-D LINE

DESCRIPTION : It is a water-borne interior, exterior and roofing primer. It prepares the surface for paint applications. It does not contain any solvents and respire; it is odor-free and resistant to alkaline. Just like topcoat applications, the primer is also anti-bacterial and prevents the surface from molding.

SOLVENT : Water

COLORS : White

PACKAGE : 20 Kg

STORAGE : If stored unopened with room temperature of +5 to +30 °C, storage life is minimum 1 year.

PREPARING THE PAINT : **The product should be mixed well before use.** Open packages should not be used and the supplier should be contacted.

PREPARING THE SURFACE: The surface should be cleaned from oil and dirt. Cracks should be filled in. Paint does not stay on lime, so the surface must be cleaned from lime.

APPLICATION TEMPERATURE: The air and surface temperature should be between +5 and +30 degrees Celsius.

APPLICATION METHOD : with brush, roll or airless gun.

APPLICATION : During primer application, for 1 kg. 50% water should be added. The application should start after the water is added. For topcoat applications, you should wait until the surface gets completely dry. Fully and properly applied primer would reinforce the performance of topcoat and reduce the amount of paint to be used for topcoat to a great extent.

DRYING TIME : Considering 20⁰ C and 65% of relative humidity rate, non-dust holding drying should take ½ hour and full drying should take 24 hours.

PAINTED AREA : For one coat, depending on the surface 8-10 m² can be painted with 1 kg.

SAFETY WARNINGS : Keep out of reach of children. Store in a cool place, best between 10 - 25 °C. Upon contact with eyes, wash with water and consult a doctor. If swallowed, immediately consult a doctor.

DANGER WARNINGS : Injurious to health when swallowed.