

### SIDING – RC LINE

**DESCRIPTION** : It is a water-borne, acrylic exterior paint modified with ceramics. It has a high resistance to water and has a water-repellent feature. It is very flexible and allows the building to respire; thus increases the physical life of the building. It is very easy to apply; resistant to bad weather conditions and corrosion. Its ceramic modification allows heat insulation. Many decorative colors can be produced.

**SOLVENT** : Water

**COLORS** : Catalogue colors

**PACKAGE** : 15 Kg

**STORAGE** : If stored unopened with room temperature of +5 to +30 °C, storage life is minimum 1 year.

**PREPARING THE PAINT** : **The product should be mixed well before use.** Open packages should not be used and the supplier should be contacted. **If a long break is given during painting, it should be mixed again before starting the application. Since the ceramic will float on the surface, mixing is very important for this product.**

**PREPARING THE SURFACE**: The surface should be cleaned from grease and dirt. Cracks should be filled in. Paint does not stay on lime, so the surface must be cleaned from lime.

**APPLICATION TEMPERATURE**: The air and surface temperature should be between +5 and +30 degrees Celsius.

**APPLICATION METHOD** : with brush, roller or airless gun.

**APPLICATION** : It is strongly suggested to use its own primer. After applying a thin undercoat, a topcoat application can be made. No water should be added; however, if necessary it can be thinned down 5%. Two coats of application is suggested; the performance would increase if the first coat is thinner and second is thicker. There should be an 8 hours of break between the two applications. **The more coats you apply the better the heat insulation will be.** The application can be made with roll, brush or spray.

**DRYING TIME** : Considering 20<sup>0</sup> C and 65% of relative humidity rate, non-dust holding drying should take 1 hour, dry to handle should take 2, 2 coats application should take 8 and full drying should take 24 hours.

- PAINTED AREA** : For both coats, depending on the surface 2-3 m<sup>2</sup> area can be painted with 1lt.
- SAFETY WARNINGS** : Keep out of reach of children. Store in a cool place, best between 10 - 25 °C. Upon contact with eyes, wash with water and consult a doctor. If swallowed, immediately consult a doctor.
- DANGER WARNINGS** : Injurious to health when swallowed.
- IMPORTANT ISSUES** : After the topcoat applications, the surface should be protected from rain and frost for at least 24 hours. If the weather and surface temperature is expected to be lower than +5 °C no application should be carried out. Performance of the product may change when applied during windy or very hot weather conditions. No other material should be added.