

### INTERIOR COATING – IC LINE

**DESCRIPTION** : It is a water-borne acrylic dispersion based interior paint modified with ceramics. It is highly water-resistant and has a water-repellent feature. It allows the surface to respire. It also prevents the surface getting moldy as a result of its anti-bacterial characteristic. It is a high-build, high-solid paint with excellent adhesion. It is easy to apply.

**SOLVENT** : Water

**COLORS** : Catalogue colors

**PACKAGE** : 15 – 5 Kg

**STORAGE** : If stored unopened in a room temperature of +5 to +30 °C, storage life is minimum 1 year.

**PREPARING THE PAINT** : **The product should be mixed well before use.** Open packages should not be used and the supplier should be contacted. **If a long break is given during painting, it should be mixed again before starting the application. Since the ceramic will condense on the surface, mixing is very important for this product.**

**PREPARING THE SURFACE**: The surface should be cleaned from grease, dirt and old paint layers. Cracks should be filled in. Paint does not stay on lime, so the surface must be cleaned from lime.

**APPLICATION TEMPERATURE**: Air and surface temperature should be between +5 and +30 degrees Celsius.

**APPLICATION METHOD** : with brush, roll or airless gun.

**APPLICATION** : It is strongly suggested to use its own primer. After applying a very thin primer, topcoat can be applied. Water should be added up to 10%. No other paint or solvent should be added to the product. Application shouldn't be made under 5°C. Two coat applications are recommended. Having a thinner first coat and thicker last coat would increase the performance. There should be a 4 hours of waiting period between the two applications. The more coats you have the better heat insulation you will get.

**DRYING TIME** : Considering 20<sup>0</sup> C and 65% of relative humidity rate, non-dust holding drying should take 1 hour, dry to handle should take 2, two coat application should take 4 and full drying should take 24 hours.

**PAINTED AREA** : For both coats, depending on the surface 4-5 m<sup>2</sup> area can be painted with 1lt.

**SAFETY WARNINGS** : Keep out of reach of children. Store in a cool place, best between 10 - 25 °C. Upon contact with eyes, wash with water and consult a doctor. If swallowed, immediately consult a doctor.

**DANGER WARNINGS** : Injurious to health when swallowed.

**IMPORTANT ISSUES:**

After the topcoat applications, the surface should be protected from rain and frost for at least 24 hours. If the weather and surface temperature is expected to be lower than +5 °C no application should be carried out. Performance of the product may change when applied during windy or very hot weather conditions. No other material should be added.