

INTERIOR COATING – MILK PAINT – IC-MP LINE

- DESCRIPTION** : It is a water-borne dispersion based interior paint. It is produced from natural raw material and called MILK PAINT. Due to its organic raw materials, it constitutes as a very healthy coating for indoors. It is highly water-resistant and has a water-repellent feature. It allows the surface to respire, thus prevents humidity. It also prevents the surface getting moldy as a result of its anti-bacterial characteristic. It has a high covering performance, strong adhesion on the surface. It's applied easily.
- SOLVENT** : Water
- COLORS** : Catalogue colors
- PACKAGE** : 20 kg – 5 Kg
- STORAGE** : If stored unopened in a room temperature of +5 to +30 °C, storage life is minimum 1 year.
- PREPARING THE PAINT** : **The product should be mixed well before use.** Open packages should not be used and the supplier should be contacted.
- PREPARING THE SURFACE**: The surface should be cleaned from grease and dirt. Cracks should be filled in. Paint does not stay on lime, so the surface must be cleaned from lime.
- APPLICATION TEMPERATURE**: Air and surface temperature should be between +5 and +30 degrees Celsius.
- APPLICATION METHOD** : with brush, roll or airless gun.
- APPLICATION** : It is strongly suggested to use its own primer. After applying a very thin primer, topcoat can be applied. Water should be added up to 25%. No other paint or solvent should be added to the product. Two coat applications are recommended. Having a thinner first coat and thicker last coat would increase the performance. There should be a 2 hours of waiting period between the two applications.
- DRYING TIME** : Considering 20⁰ C and 65% of relative humidity rate, non-dust holding drying should take 1 hour, dry to handle should take 2, two coats application should take 4 and full drying should take 24 hours.
- PAINTED AREA** : For both coats, depending on the surface 5-6 m² area can be painted with 1lt.

SAFETY WARNINGS : Keep out of reach of children. Store in a cool place, best between 10 - 25 °C. Upon contact with eyes, wash with water and consult a doctor. If swallowed, immediately consult a doctor.

DANGER WARNINGS : Injurious to health when swallowed.

IMPORTANT ISSUES:

After the topcoat applications, the surface should be protected from rain and frost for at least 24 hours. If the weather and surface temperature is expected to be lower than +5 °C no application should be carried out. Performance of the product may change when applied during windy or very hot weather conditions. No other material should be added.